



EXTREEM LED TECH

WWW.FLASHPATTERNS.NL

Installation Instructions

Surface Mount.

+ve VDC

Chassis Ground

Flash pattern select and synchronisation

Alternate flash

- Red
- Black
- Green
- White

To select Flash Pattern:-

Momentarily apply +ve VDC to Green wire, once for next pattern.

Touch and hold for 5 seconds to reset to FP#1 (Double Flash R65 Class 1).

Synchronous flash:-

Set all lights to the same flash pattern, connect the green wires together.

Alternate flash:-

Set all lights to the same flash pattern, connect green wires together. Connect white wire from one light to positive and lights will flash alternately.

To synchronise multiple lights connect all the green wires together.

To alternate groups of lights, connect all the green wires together and then connect the white wires to positive, (from the lights you wish to alternate).

Pattern	Flash Mode	Rate
1	Single Flash, ECE R65 Class 1 (by night)	125FPM
2	Single Flash, California Title 13	75FPM
3	Double Flash	125FPM
4	Triple Flash	125FPM
5	Quadruple Flash	125FPM
6	Quintuple Flash	125FPM
7	Combination Single/Double Flash	
8	Combination Single/Triple Flash	
9	Combination Single/Quintuple Flash	
10	Strobe	600FPM
11	Cruise(30% brightness by night)	

